



## Product Specification Sheet

### **TS/6-62:100.**

PreMoist Swab - Polystyrene shaft/Viscose Swab, pre-moistened in de-ionised water sealed in tube

Product Code	TS/6-62:100.
Description	PreMoist Swab - Polystyrene shaft/Viscose Swab, pre-moistened in de-ionised water sealed in tube
Intended Use	Environmental sampling, Not suitable for prolonged transport, cleaning validation or hygiene monitoring unless samples are processed on growth media with neutralisers immediately.
Components	Polypropylene Tube, Blue HDPE Standard Cap, Polystyrene/viscose tip swab, Label, hot melt glue.
Contents	De-ionised Water - 1 Litre
Method of Sterilisation	Sterilised by gamma irradiation at dosage of 25-53.4kGy
Shelf Life	24 months from date of manufacture
Storage Conditions	4-25°C. Store in dry and ventilated area; protect from light, heat and moisture in tightly closed original packaging
Precautions and Limitations	Analyse as soon as possible due to the small volume, so to minimise sample dryout and organism loss. Refrigeration will stabilise recovery of some organisms. Not suitable for most fastidious organism unless analysed immediately.
Pack Size	100 in a box
Other	Quality control testing details on final product: i) Validation of irradiation sterility ii) Product appearance.

This specification (and formulation where applicable) are intended for guidance only and may be adjusted to meet product defined criteria.

You should always refer to a professional with experience in your intended application if in any doubt.

Issue #: 3 Date: 09.02.2023  
ProductSpec\_TS6-62:100.